



NEW 2011 SUPPORT STAND Certification requirements

All Gray Support Stands "certified" to meet 2011 P.A.L.D.
"Portable Automotive Lifting Devices" (P.A.L.D.) Standards as provided
by the AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)



Specifications	7-TF	7-THF
Capacity (each)	15,435lbs	15,435lbs
Min. Start Height	9 ½"	12"
Max. Lift Height	16"	20"
Adjustments	1"	1 ½"
Shipping Weight	32lbs	38lbs
Specifications	10-TF	10-THF
Capacity (each)	20,000lbs	20,000lbs
Min. Start Height	20"	30 "
Max. Lift Height	32"	52"
Adjustments	1"	1"
Shipping Weight	70lbs	158lbs
Specifications	25-TF	25-THF
Capacity (each)	50,000lbs	50,000lbs
Min. Start Height	12"	20"
Max. Lift Height	20"	32"
Adjustments	1 ½"	1 ½"
Shipping Weight	62lbs	112lbs
Specifications	35-TF	35-THF
Capacity (each)	70,000lbs	70,000lbs
Min. Start Height	13 ½"	21"
Max. Lift Height	21"	33 ¼"
Adjustments	2"	2"
Shipping Weight	84	129



GRAY – All Gray Products are made in the U.S.A. 

The latest new products can be viewed in the "on-line catalog" @ www.grayusa.com website

Distributed By:



Clifford Underwood Hydraulique
 8445 rue Lafrenaie, St-Léonard, Montreal, QC H1P2B3
 514-325-5210 1-800-363-5438
cliffordunderwood.com