

HEAVY DUTY COMPONENT JACKS

- Head rotates 360° allowing flexibility and convenience during installation and removal of clutches
- Hydraulic power system provides precise adjustment
- Swivel casters permit easy movement
- Fold back feature allows technician to remove jack from underneath the vehicle



Flywheel Adapter

Optional Adapters Available:

- 1-3/4" Spline for 1" or .983" hub pilot sizes
- Flywheel adapter

Model TCJ-500 only

- 12" height extension adapter
- Brake Drum Hub adapter



HR-300
300 lb Capacity
High Rise Model



Battery Tray



U.S. Patent #
6,189,864,B1

TCJ-500
300 lb Capacity
Floor Model

SPECIFICATIONS	TCJ-500
Capacity	300 lbs.
Minimum Start Height	15"
Maximum Lift Height	39"
Overall Width	22"
Overall Length	41"
Supplied Spline Shaft	2"
Swivel Caster Diameter	3"
Head Rotation	360°
Shipping Weight	134 lbs.

Manufactured in USA
Specifications are subject to change without notice.



- Foot pedal controls allow hands-free operation
- 2-stage design: 1st stage 100% air operated for speed; 2nd stage hydraulic for precise control



SPECIFICATIONS	HR-300
Capacity	300 lbs.
Minimum Start Height	40"
Maximum Lift Height	80 1/2"
Power	1st Stage - Air 2nd Stage - Hydraulic
Head Rotation	360°
Width	41"
Length	41"
Supplied Spline Shaft	2"
4 Swivel Casters	4"
Required Air Pressure	100-160 PSI
Shipping Weight	105 lbs.

Manufactured in USA
Specifications are subject to change without notice.