



HEAVY DUTY FORKLIFT JACKS

- Low Starting Height of 2 1/4"
- The industry leader for nearly 40 years!

FLJ-400
4 Ton Capacity

FLJ-770
7 Metric Ton Capacity

SPECIFICATIONS	FLJ-400C	FLJ-400 A/H	FLJ-770B	FLJ-770 A/H
Capacity	8,000 lbs	8,000 lbs	15,442 lbs	15,442 lbs
Maximum Lift Height	16"	16"	16"	16"
Power	Hydraulic	Air/Hydraulic	Hydraulic	Air/Hydraulic
Required Air Pressure	N/A	155 PSI	N/A	155 PSI
Reach (Raised Position) (Distance from Hydraulic Cylinder to Lift Pad)	7"	7"	7"	7"
Width	8"	8"	10"	10"
Starting Pad Height (Lift Arm Notch)	2 1/4"	2 1/4"	2 1/4"	2 1/4"
Starting Pad Height (Serrated Lift Pad)	2 1/2"	2 1/2"	2 1/2"	2 1/2"
Shipping Weight	68 lbs	71 lbs	93 lbs	98 lbs

Manufactured in USA • Specifications are subject to change without notice.

Air/Hydraulic Powered Models Now Available



Hold-to-Run™ Release Knob provides slower descent rate with precise operator control



Two-Position Lift Pad easily adjusts to handle flat or edged surfaces



Use with
Model 7-TF
Vehicle Support
Stands
(see page 14)



Forklift using WPLS and Forklift Adaptors