

HIGH PERFORMANCE TIRE CHANGERS

*SWING ARM DESIGN -
HANDLES TIRES TO 47"
DIAMETER AND RIM
WIDTHS TO 15".*

*This model has power
to spare and a 26" x 26"
square turntable that can
handle wheel diameters
up to 47" with ease.*

TC-950WPA
High performance
Automatic
Tire changer
with press arm



Features:

- ◆ Swing arm design
- ◆ Handles tires to 47" and rim widths to 15"
- ◆ Four pneumatic clamps and double acting cylinders
- ◆ Side mounted bead breaker
- ◆ Press arm for low profile tires
- ◆ Bead seating inflation jets in clamping jaws
- ◆ No scratching. Machine never contacts rim
- ◆ Lubricator, separator and air pressure regulator

SPECIFICATIONS:	TC-950WPA
Max wheel diameter	47"
Max wheel width	3" - 15"
Rim diameter inside	15" - 28"
Rim diameter outside	13" - 24"
Working pressure	10 bar
Power supply	1 ½ hp 110 vac
Bead breaker	2500 kg

TC-960
High performance
Fully-automatic
Tire changer
with press
arm and rollers



Features:

- ◆ Large square turn table
- ◆ Tilting column and pneumatic locking system
- ◆ Bead seating inflation jets are integrated in the clamping jaws for quick and safe inflation
- ◆ Twin clamping cylinders provide more power to hold the most difficult rims
- ◆ Conveniently located powerful bead breaker
- ◆ No scratching - machine never contacts rim
- ◆ Large diameter hex mount /demount shaft for extra rigidity
- ◆ Pressure regulator, oiler and water separator standard
- ◆ Assist arm for changing stiff low-profile tires. All the bell and whistles to take the work out of low profile tire repairs

SPECIFICATIONS:	TC-960
External clamping	13" - 24"
Internal clamping	15" - 28"
Max wheel diameter	47 ½"
Wheel width	3" - 15"
Bead breaker	2500 kg
Operating pressure	110 - 147 psi