



# WHEEL LIFT SYSTEMS

- Portable design eliminates the need for a dedicated bay
- No more time wasted removing aerodynamics or ferrings from the vehicle
- Perfect solution for shops with low ceilings
- 100% Air Operated



U.S. Patent # D357,106 & 5,484,134

Lifts one end of a wide array of vehicles, fire or refuse trucks, heavy recreational vehicles or motor coaches. Wide, spring loaded base provides stable platform for secure lifting.



SPECIFICATIONS	WL-40	WL-30	WL-20
Capacity per Set of Two	40,000 lbs	30,000 lbs	20,000 lbs
Minimum Start Height	Floor Level	Floor Level	Floor Level
Maximum Lift Height	30"	24"	24"
Power	Shop Air	Shop Air	Shop Air
Required Air Pressure	160 PSI	160 PSI	160 PSI
Stroke	30"	24"	24"
Minimum Wheel Diameter (w/Adaptors)	14"	16"	16"
Minimum Wheel Diameter (w/o Adaptors)	21"	19 1/2"	19 1/2"
Maximum Wheel Diameter	24 1/2"	24 1/2"	24 1/2"
Overall Width	45"	41 9/16"	41 9/16"
Overall Depth	44"	44 1/4"	44 1/4"
Overall Height	63"	53 1/4"	53 1/4"
Shipping Weight	1,965 lbs	1,500 lbs	1,000 lbs

Manufactured in USA • Specifications are subject to change without notice.





### WL-40 features:

- Easily handles wheel sizes from 21" to 24.5"
- Small Wheel Adapters Included to accommodate 14" to 21" wheels

### WL-20 & WL-30 features:

- Easily handles wheel sizes 19.5" to 24.5"
- Optional small wheel adapters available to accommodate 16" to 19.5" wheels



**WL-40**  
20 Ton Capacity



**WL-30**  
15 Ton Capacity



**WL-20**  
10 Ton Capacity



Built-in vehicle support stand feature allows complete open access under the vehicle.

## FEATURES



Small Wheel Adapters



Dual trigger control valve allows synchronized raising and lowering of vehicle.