



HEAVY DUTY FLOOR SERVICE JACKS

- A low start height combined with a high lift height accommodates a variety of vehicles
- Heavy duty steel frame design stands up to the most vigorous shop use
- Manual pump feature included
- Large front wheels and long-life heavy duty rear swivel casters allows ease of portability and durability

SPECIFICATIONS	FSJ-120	FSJ-200
Max. Capacity	12,000 lbs	20,000 lbs
Min. Start Height	4 3/4"	7"
Max. Lift Height	23 1/4"	27"
Power	Air/Hydraulic/Manual	
Required Air Pressure	90-175 PSI	90-175 PSI
Chassis Height	9 3/4"	10"
Chassis Length	48"	53 1/2"
Handle Length	47 3/4"	47"
Overall Width	18 1/2"	21 7/8"
Overall Length	95 1/4"	101 3/4"
Overall Reach	87"	93"
Front Caster Diameter	4 1/3"	5"
Rear Swivel Caster Diameter	4"	4"
Saddle Diameter	7 3/8"	8"
Front Width Caster to Caster	16 7/8"	17 1/8"
Rear Width Bracket to Bracket	19 7/8"	20 1/8"
Shipping Weight	256 lbs.	410 lbs.

Manufactured in USA
Specifications are subject to change without notice.

FSJ-120
6 Ton Capacity

FSJ-200
10 Ton Capacity

Gray Vehicle Support Stands shown in use (page 14).

**3 Ton Manual/Hydraulic
Powered Model
Also Available!**

